

AD-A106 746

NAVAL SURFACE WEAPONS CENTER DAHLGREN VA

F/8 19/6

GAS-SUN PLANAR IMPACT STAGING EXPERIMENTS FOR FLYER PLATE VELOC--ETC(U)

APR 81 W H HOLT, W MOCK

UNCLASSIFIED

NSWC/TR-80-368

NL

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

1001

END

DATE

FILMED

12-81

DTIC

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER NSWC/TR-80-368	2. GOVT ACCESSION NO. AD A106	3. RECIPIENT'S CATALOG NUMBER 746	
4. TITLE (and Subtitle) GAS GUN PLANAR IMPACT STAGING EXPERIMENTS FOR FLYER PLATE VELOCITY ENHANCEMENT.	5. TYPE OF REPORT & PERIOD COVERED Final rept.		
7. AUTHOR(s) William H. Holt Willis Mock, Jr.	6. CONTRACT OR GRANT NUMBER(s)		
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Surface Weapons Center (G30) Dahlgren, VA 22448	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62332NIE32392 SF32392391		
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Sea Systems Command Washington, DC 20362	12. REPORT DATE April 1981		
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	13. NUMBER OF PAGES 28		
	15. SECURITY CLASS. (of this report) UNCLASSIFIED		
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE		
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Gas gun Impact Staging Stress waves			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Gas gun impact experiments and computational simulations were performed to investigate a technique for increasing flyer plate velocities. Stainless steel impactors, PMMA and aluminum buffers, and stainless steel flyers were used. Charged contact pins were used to measure impactor and flyer velocities. The velocities of the flyers were on the order of 1.5 times the impactor velocities, in agreement with computational results.			

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-LF-014-6601

UNCLASSIFIED


SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

411567

LB

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

FOREWORD

This report describes impact experiments performed with the NSWC gas gun to investigate a technique for increasing flyer plate velocities. This work was supported by NAVSEA Block No. SF-33-354-391.

This report has been reviewed and approved by C. A. Cooper, Head, Gun Systems and Munitions Division.

Released by:

R. P. Fuscald

CAPT R. P. FUSCALDO
Assistant for Weapons Systems
Weapons Systems Department

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

ACKNOWLEDGEMENTS

The authors wish to acknowledge J.A. Forbes and J. O. Erkman for helpful discussions and for performing WONDY computer simulations for the impact experiments.

CONTENTS

	Page
FOREWORD.....	iii
ACKNOWLEDGEMENTS.....	v
LIST OF ILLUSTRATIONS.....	viii
LIST OF TABLES.....	viii
I. INTRODUCTION.....	1
II. EXPERIMENTAL DETAILS	2
III. RESULTS AND SUMMARY.....	7
REFERENCES	10
APPENDIXES	
A – OSCILLOSCOPE RECORDS OF PIN CLOSURE PULSES FOR FLYER VELOCITY MEASUREMENTS	A-1
B – POSTSHOT PHOTOGRAPHS OF A STAINLESS STEEL IMPACTOR AND A STAINLESS STEEL FLYER	B-1
DISTRIBUTION	

LIST OF ILLUSTRATIONS

Figures		Page
1	Schematic of planar impact staging	1
2	Schematic of gas gun	3
3	Schematic of the muzzle region of the gas gun with a target configuration for an impact staging experiment	3
4	Photograph of an unassembled target configuration	5
5	Photographs of an assembled target configuration	6
6	Calculated impactor and flyer velocities as a function of time after impact for Shot 161	9
7	Calculated impactor and flyer velocities as a function of time after impact for Shot 162	9
A-1	Oscilloscope record of flyer velocity pin closure pulses for Shot 161	A-3
A-2	Oscilloscope record of flyer velocity pin closure pulses for Shot 162	A-3
B-1	Postshot photographs of the recovered stainless steel impactor and stainless steel flyer for Shot 161	B-3

LIST OF TABLES

Table		Page
1	Data summary for planar impact staging experiments	8

1. INTRODUCTION

This report describes gas gun experiments and computational simulations for planar impact staging to achieve high velocities for flyer plates. Staging techniques take advantage of multiple wave interactions in impacted layered targets and have been the subject of several experimental and analytical studies.¹⁻³ For certain conditions the velocity of the flyer plate (the target layer farthest from the impact plane) can be greater than that of the impactor plate (see Figure 1) by 60% or more.³




Figure 1. Schematic of planar impact staging. V_1^{Impactor} and V_2^{Impactor} are the initial and final velocities of the impactor, respectively. V_1^{Flyer} and V_2^{Flyer} are the initial and final velocities of the flyer, respectively. For certain combinations of the materials and relative thicknesses of the impactor, buffer, and flyer, V_2^{Flyer} can be greater than V_1^{Impactor} . The shock impedance of the buffer is assumed to be less than that of the impactor or flyer.

Explosive plane wave lens experiments² and two-stage light gas gun experiments³ have demonstrated this effect with impactors and multilayered targets consisting of materials having a wide range of shock impedances, from high-impedance tantalum to low-impedance lithium. The layered targets were constructed so that the layers of "buffer" material (between the impactor and the final "flyer" layer) were arranged in order of decreasing shock impedance and the thicknesses of the buffer layers were selected so that the stress wave transit times in the layers were approximately the same.

The impact experiments described in this report were performed with the NSWC gas gun⁴ for simple one- and two-layer buffers, using common materials: 304 stainless steel, 6061-T6 aluminum and polymethyl methacrylate (PMMA) (trade-named Lucite or Plexiglas). These experiments are described in Section II and the results are presented in Section III. Oscilloscope records for velocity measurements of the stainless steel flyers are provided in Appendix A. Appendix B contains postshot photographs of a stainless steel impactor disc and a stainless steel flyer disc.

II. EXPERIMENTAL DETAILS

Type 304 stainless steel was selected for the high impedance impactor and flyer materials because of its relatively low Hugoniot elastic limit ($\sim 0.23 \text{ GPa}$)⁵ and the absence of shock-induced phase transitions^{5,6} in the stress range for the present experiments and for potential future experiments at higher impact velocities. These properties should result in a relatively low amplitude elastic wave and only a single plastic wave generated initially in the impactor and flyer, thereby simplifying the interpretation of the experimental results. The PMMA and 6061-T6 aluminum buffer materials were selected on the basis of their shock impedances being less than that of stainless steel and on the availability of Hugoniot and related material properties data.⁵⁻⁸

Figure 2 is a schematic of the 40-mm-bore gas gun used for these experiments. Figure 3 is a schematic of the muzzle region of the gun. The impactor disc is carried in a recess in the front of the projectile. The buffer and flyer discs were held together by a thin layer of adhesive (Homalite 1100) and were held in the target holder by epoxy (Castall 300-RT7). The epoxy potting of the target assembly was accomplished on a precision granite surface plate (coated with a thin layer of

fluorocarbon mold release agent). This was to ensure the planarity of the buffer and flyer combination with the surface of the target holder that would be in contact with the target mounting flange of the gas gun.




Figure 2. Schematic of gas gun.




Figure 3. Schematic of the muzzle region of the gas gun with a target configuration for an impact staging experiment. The impactor disc is carried on the front of the projectile and impacts the buffer disc that is in contact with the flyer disc. After the flyer disc has moved a distance of approximately 6.4 mm, its velocity is measured with the array of charged velocity pins. The velocity of the projectile and impactor prior to impact is measured with the charged pins in the side of the barrel.

A set of four flyer velocity measurement pins positioned at 90° intervals on a 12.6-mm-diameter circle around a central grounding pin were mounted in a Lucite and epoxy holder behind the flyer. A Lucite mold (coated with layer of vacuum grease) was used to fabricate the velocity pin holder. The pins were made from 50-mm lengths of 0-80 UNF stainless steel threaded rod; one end of each rod was lapped perpendicular to the rod axis. The threads were coated with a fluorocarbon mold release agent prior to being potted in the epoxy; this permitted turning of the rods in the cured epoxy to adjust the relative positions of the pin tips. After the buffer and flyer discs were secured in the target holder, a precision 6.35-mm-thick copper spacer disc was placed on the back side of the flyer. The holder for the pins was then secured to the target holder by two 10-32 UNF screws. The grounding pin was then adjusted until it contacted the spacer disc. The pin holder was then demounted from the target holder and mounted on a special granite fixture⁴ for precision positioning of the velocity pin tips. A dial indicator height gauge with 0.002-mm resolution (Scherr-Tumico Model BL5) was used to measure the relative heights of the velocity pin tips from the plane of the tip of the ground pin.

Two of the velocity pin tips (at 0 and 180° positions) were adjusted to be 0.51 ± 0.02 mm below the plane of the ground pin tip. The remaining two pin tips (at 90° and 270° positions) were adjusted to be 0.51 ± 0.02 mm below the plane of the first pair of pin tips. All the pins were then secured with fast setting epoxy (Hardman 8173). The pins were connected by coaxial cables to time-of-contact measurement circuits.⁹ The four velocity pins were electrically charged and have the voltage ratios 6:3:2:1, respectively. These ratios are used to distinguish between the grounding closure of each of the four pin circuits. (The flyer contacts the ground pin first to ensure proper pin pulse responses).

Figure 4 shows an unassembled target configuration. The target holder containing a buffer and flyer disc combination is shown in front of the velocity pin holder. Figure 5 shows views of an assembled target configuration.






Figure 4. Photograph of an unassembled target configuration. The target holder containing a buffer and flyer combination is shown in front of the velocity pin holder. The array of four velocity pins and the central grounding pin can be seen protruding from the epoxy part of the velocity pin holder. The coaxial cables connect the velocity pins to the charging and contact sensing circuits.



(a)



(b)

Figure 5. Photographs of an assembled target configuration. (a) Side view showing the impact surface of the buffer disc (at left of target holder) and the concentric annular surface of the target holder that contacts the target mounting flange of the gas gun. (b) Back view showing attachment of velocity pins to the coaxial cables.

III. RESULTS AND SUMMARY

The details of the planar impact staging experiments are presented in Table 1. The impactor discs were 35.6-mm-diameter, 5.0-mm-thick, 304 stainless steel. For Shot 161, with a single 3-mm-thick PMMA buffer layer and a 1-mm-thick stainless steel flyer, the measured flyer velocity was 1.40 times the initial velocity of the impactor. For Shot 162, the 3-mm-thick buffer consisted of a 1.8-mm-thick aluminum alloy layer and a 1.2-mm-thick PMMA layer; the measured velocity of the 1-mm-thick stainless steel flyer was 1.59 times the initial velocity of the impactor.

The SRI PUFF 8 one-dimensional stress wave propagation computer program⁷ was used to calculate the velocities of the material layers. Figures 6 and 7 show the calculated impactor and flyer velocities as a function of time after impact for Shots 161 and 162, respectively. The calculated and measured velocities for the stainless steel flyers agree to within 10%. Calculations with the Sandia Laboratories WONDY IV computer program¹⁰ gave very similar results.¹² The PUFF 8 calculations indicate that the stainless steel impactor velocities for Shots 161 and 162 decreased by an average of about 53% after impact. The calculated final velocity for the aluminum alloy buffer layer (Shot 162) indicated that the metal part of the buffer was accelerated to within 17% of the impactor initial velocity.

In summary, it has been demonstrated that for these simple one- and two-layer buffer planar staging configurations it is possible to launch metal flyer layers at velocities approximately 1.5 times that of the initial impactor velocity.

Table 1. Data summary for planar impact staging experiments.

Shot No.	Impactor ^a			Buffer ^a			Flyer ^a			Flyer/Impactor Velocity Ratio ^e	
	Material	Thickness (mm)	Impact Velocity ^b (km/s)	Final Velocity ^c (km/s)	6061-T6 Aluminum		PMMA Thickness (mm)	Thickness (mm)	Measured Velocity ^d (km/s)		
					Thickness (mm)	Velocity ^c (km/s)					
161	304 stainless steel	5.0	0.89	0.43	f	f	3.0	1.0	1.25	1.38	1.40
162	304 stainless steel	5.0	0.88	0.41	1.8	0.73	1.2	1.0	1.40	1.30	1.59

^a The impactor diameters were all 35.6 mm. The buffer and flyer diameters were all 27.9 mm.

^b Average of two velocity measurements, each over 10-mm distance, just prior to impact.

^c Calculated using the SRI PUFF 8 one-dimensional stress wave propagation computer program. ⁷ For Shot 161, the number of computational cells for the impactor, buffer, and flyer were 10, 6, and 4, respectively. For Shot 162, the number of computational cells for the impactor, aluminum buffer layer, PMMA buffer layer, and flyer were 10, 4, 3, and 4, respectively. The 304 stainless steel Hugoniot and associated data for the computations were obtained from Reference 5; the yield strength was obtained from Reference 8. The 6061-T6 aluminum and PMMA Hugoniot and associated data including yield strength were obtained from Reference 7. Calculations using the Sandia WONDY IV computer program¹⁰ gave very similar results. The Hugoniot and associated data were obtained from References 6 and 11 (the aluminum Hugoniot data used in WONDY IV was for 2024 alloy); spall strengths of 5 GPa and 0.5 GPa were used for the metals and PMMA, respectively. ¹² For Shot 161 the number of computational cells used in WONDY IV for the impactor, buffer, and flyer layers were 50, 30, and 20, respectively. For Shot 162 the number of cells for the impactor and flyer were the same as for Shot 161; there were 18 and 30 cells in the aluminum and PMMA buffer layers, respectively. ¹²

^d Measured with charged impact pins over a distance of 0.51 mm, after the flyer has moved 6.36 mm. Prior to the time of measurement the flyer had separated from the buffer and was essentially in an unstressed state, according to WONDY IV calculations.

^e Ratio of the measured velocity of the flyer to the velocity of the impactor just prior to impact.

^f No aluminum buffer layer was used in this experiment.




Figure 6. Calculated impactor and flyer velocities as a function of time after impact for Shot 161.




Figure 7. Calculated impactor and flyer velocities as a function of time after impact for Shot 162.

REFERENCES

1. A. S. Balchan, and G. R. Cowan, "Method for Accelerating Flat Plates to High Velocity," *Review of Scientific Instruments*, Vol. 35, p. 937 (1964).
2. V. I. Laptev and Yu. A. Trishin, "Increasing Initial Velocity and Pressure on Impact with an Inhomogeneous Obstacle," *Journal of Applied Mechanics and Technical Physics*, Vol. 6, p. 128 (1974).
3. G. R. Fowles, C. Leung, R. Rabie, and J. Shaner, "Acceleration of Flat Plates by Multiple Staging," *High Pressure Science and Technology*, 6th AIRAPT Conference (Boulder, Co., July 25-29, 1977). Vol. 2, p. 911 (1979).
4. W. Mock, Jr. and W. H. Holt, *The NSWC Gas Gun Facility for Shock Effects in Materials*, NSWC TR-3473 (Dahlgren, Va., July 1976).
5. B. J. Kohn, *Compilation of Hugoniot Equations of State*, AFWL-TR-69-38, Air Force Weapons Laboratory, Kirtland Air Force Base, (N. M. April 1969).
6. R. G. McQueen, S. P. Marsh, J. W. Taylor, J. N. Fritz, and W. J. Carter, "The Equation of State of Solids from Shock Wave Studies," *High Velocity Impact Phenomena*, edited by R. Kinslow, (New York: Academic Press, 1970) p. 293.
7. L. Seaman and D. R. Curran, "SRI PUFF 8 Computer Program for One-Dimensional Stress Wave Propagation," Final Report, Vol. 2, SRI International, Contract Report ARBRL-CR-00420, U. S. Army Ballistic Research Laboratory (Aberdeen Proving Ground, Md., March 1980).
8. F. W. Wilson and P. D. Harvey, Editors, *Tool Engineers Handbook* (New York: McGraw-Hill Book Company, 1959).
9. E. J. Shuler, W. Mock, Jr., and W. H. Holt, "Electronic Circuit Using Charged Pins for Determining Impact Planarity in Shock Wave Experiments," *Review of Scientific Instruments*, Vol. 45, p. 203 (1974).
10. R. J. Lawrence and D. S. Mason, "WONDY IV - A Computer Program for One-Dimensional Wave Propagation with Rezoning," SC-RR-710284, Sandia Laboratories (Albuquerque, N. M., August 1971).
11. R. J. Lawrence, D. S. Mason, and S. E. Benzley, "Dynamic Material Property Library," SC-DR-68-885, Sandia Laboratories (Albuquerque, N. M., December 1968).
12. J. O. Erkman, private communication, Naval Surface Weapons Center (March 1979).

APPENDIX A

**OSCILLOSCOPE RECORDS OF PIN CLOSURE
PULSES FOR FLYER VELOCITY
MEASUREMENTS**




Figure A-1. Oscilloscope record of flyer velocity pin closure pulses for Shot 161. The vertical scale is 2 v/div and the horizontal scale is 0.1 μ s/div. A 0.02- μ s period time calibration wave is shown at the bottom.





Figure A-2. Oscilloscope record of flyer velocity pin closure pulses for Shot 162. The vertical scale is 2 v/div and the horizontal scale is 0.1 μ s/div. A 0.02- μ s period time calibration wave is shown at the bottom.

APPENDIX B

**POSTSHOT PHOTOGRAPHS OF A STAINLESS
STEEL IMPACTOR AND A STAINLESS
STEEL FLYER**




(a)



(b)

Figure B-1. Postshot photographs of the recovered stainless steel impactor and stainless steel flyer for Shot 161. (a) Surfaces that impacted the flyer velocity pins. (b) Opposite surfaces. (c) Edge view; direction of motion of impactor and flyer was from left to right in the figure.



(c)

Figure B-1 (Continued).

DISTRIBUTION

Commander

Naval Sea Systems Command

Washington, DC 20360

ATTN: SEA-003 (S. R. Marcus)
SEA-05R (G. N. Sorkin)
SEA-05R22 (S. J. Matesky)
SEA-62R (W. W. Blaine)
SEA-62R31 (R. A. Bailey)
SEA-62R32 (G. Edwards)
SEA-62R54 (B. Lubin)
SEA-62Y13C (L. H. Hawver)
SEA-62Z3 (J. Whelan)
SEA-62R4 (M. A. Kinna)

Commander

Naval Air Systems Command

Washington, DC 20360

ATTN: AIR-310B (J. W. Willis)
AIR-320 (T. F. Kearns)
AIR-350 (H. B. Benefiel)
AIR-5163 (C. Bersch)
AIR-5324 (S. Englander)

Office of Naval Technology

Department of the Navy

Boston Towers Bldg. No. 1

800 N. Quincy St.

Arlington, VA 22217

Office of Naval Research

Department of the Navy

Washington, DC 20360

ATTN: ONR-420 (T. G. Berlincourt)
ONR-465 (E. I. Salkovitz)

Office of Naval Research

536 S. Clark St.

Chicago, IL 60605

ATTN: George Sandoz

Office of Naval Research

Bldg. 114 Section D

666 Summer St.

Boston, MA 02210

ATTN: L. H. Peebles, Jr.

DISTRIBUTION (Continued)

Los Alamos Scientific Laboratory

Los Alamos, NM 87544

ATTN: S. A. Colgate

J. M. Holt, Jr.

R. Morales

J. A. Morgan

J. Shaner

Technical Library

(2)

Sandia Laboratories

Albuquerque, NM 97115

ATTN: Lee Davison

R. A. Graham

Technical Library

(2)

Lawrence Livermore Laboratory

University of California

Livermore, CA 94550

ATTN: S. Cochran

W. H. Gust

E. Nidick, Jr.

New Mexico Institute of Mining and Technology

Campus Station

Socorro, NM 87801

ATTN: P. D. Buckley

H. L. Giclas

M. L. Kempton

SRI International

333 Ravenswood Avenue

Menlo Park, CA 94025

ATTN: D. Curran

L. Seaman

Shock Dynamics Laboratory

Washington State University

Pullman, WA 99163

ATTN: G. E. Duvall

G. R. Fowles

DISTRIBUTION (Continued)

Commander
Naval Research Laboratory
Washington, DC 20375
ATTN: 7908 (A. Williams)

Commander
Naval Weapons Center
China Lake, CA 93555
ATTN: M. E. Backman
R. L. Ballenger
J. Pearson
H. Pieper
E. B. Royce
R. G. Sewell
T. Zulkoski

Director
Army Ballistic Research Laboratory
Aberdeen Proving Ground, MD 21005
ATTN: W. S. deRosset
W. Gillich
F. I. Grace
G. E. Hauver
G. Moss
R. Vitali

Commander
Army Materials and Mechanics Research Center
Watertown, MA 92172
ATTN: D. T. Dandekar
J. F. Mescall

Commander
Army Research and Development Command
Dover, NJ 07801
ATTN: F. J. Owens

Commander
Army Engineer Waterways Experiment Station
Corps of Engineers
Vicksburg, MS 39180
ATTN: D. R. Coltharp

DISTRIBUTION (Continued)

**GIDEP Operations Office
Corona, CA 91720**

**Defense Technical Information Center
Cameron Station
Alexandria, VA 22314**

(12)

**Defense Printing Service
Washington Navy Yard
Washington, DC 20374**

**Library of Congress
Washington, DC 20540
ATTN: Gift and Exchange Division**

(4)

Local:

**C
D
E41
F
F10
F12 (Berger)
G
G10
G102
G103
G11
G11 (Torgrimson)
G13
G13 (Wasmund)
G13 (Hock)
G13 (Dickinson)
G20
G21 (Donalson)
G25
G25 (Bolt)
G25 (Elliott)
G25 (Hales)
G25 (D. Smith)**

DISTRIBUTION (Continued)

G25 (T. Smith)
G25 (Womack)
G30
G301
G302
G31
G32
G33
G35
G35 (Adams)
G35 (Mock)
G35 (Holt)
G35 (Peterson)
G35 (Wishard)
G35 (Waggener)
G40
G50
G60
K21
K21 (*Blackmon*)
R
R04
R10
R12
R122 (Roslund)
R12 (Erkman)
R12 (Lutzky)
R12 (Short)
R13
R13 (Coleburn)
R13 (Forbes)
R15
R15 (Hammond)
R16 (Dengel)
R30
R31
R32
X210